
laborstrauss.com

- > Intelligent remote tableau for Fire Detection Control Panels Series BC08
- > Indication of the events and operating conditions of a fire detection system
- > Remote operation of important system functions
- > 3 freely parametrerisable inputs
- > 2 optional key switches
- > Integrated extinguishing keys



The events are displayed as text on a four-line illuminated LC display and with corresponding individual displays (LEDs), as on the control panel Series BC08.

The operation of the control panel possible on the Remote Tableau SG08 in two authorisation levels (e.g. silencing the buzzer of the control panel, switching the intervention on or off) largely corresponds to the operating procedures on the control panels Series BC08, so that the operator very quickly becomes familiar with the functions of the remote tableau.

Up to three external contacts can be connected to the signalling device in addition to the 2 possible key switches on the front panel of the signalling device.

The connection to the control panel Series BC08 is made via the SIGNAL bus. Up to 6 Remote Tableaus SG08 can be connected to one control panel. The power supply lines of the Remote Tableau SG08 can be designed to be non-reactive.

TECHNICAL DATA

Operating voltage	from 12 VDC to 30 VDC
Current consumption typ.	25 mA (at 24 V, quiescent condition)
Current consumption max.	100 mA (at 24 V, fault condition of the three inputs)
Relative humidity (no condensation) max.	95 %
Protection class	IP30
Ambient temperature	from -5 °C to 40 °C
Mounting type	surface mounting
Casing material	sheet steel, 1 mm, powder coated
RAL colour	grey white, RAL 9002
Dimensions W \times H \times D	250 × 174 × 30 mm





Remote Tableau SG08-1



Weight	0.45 kg
Article number	250080
Order reference	Remote Tableau SG08-1



Certified to ISO 9001 and ISO 14001