

Manual Call Points Conventional for fire detection systems

- **Conventional technology**
- **Optionally available with second change-over contact**
- **LED indicates activation**
- **Operating instructions in the form of standardised symbols (EN 54-11)**
- **Attractive design housing made of robust die-cast aluminium**
- **Optionally available with protection class IP65, or upgradeable to IP54**



Description

The manual call points according to EN 54-11 / type B are connected to the fire detection or extinguishing control panel via a conventional detector line.

The version with a second switch contains an independent dry change-over contact by means of which additional switching actions can be carried out in the event of activation.

The red status LED optically indicates the activated condition of the device.

In comparison with plastic cases, the robust design housing made of die-cast aluminium proves to be of advantage even after years of use, thanks to its resistance to environmental impact: It is virtually unbreakable, form stable and hardly changes its colour in sunlight.

Numerous design details, such as the self-closing lock cover, protect the interior from dust or water penetra-

tion and facilitate mounting and cabling. The protection class IP43 can be increased to IP54 by means of the optional Protection Kit HME-ZS-IP54. For use under harsh environmental conditions, the manual call points are also available with protection class IP65.


The door with the easily replaceable glass pane has an opening angle of over 180°. When the call point is activated, the door is mechanically prevented from closing.

The manual call points are available with a standardised symbol printed on them or with a changeable label. Requirement-specific changeable door labels are available on request.

Accessories

The accessories for the Manual Call Points Series HME are described in detail in the data sheet **HME-Accessories_DBL_LST_EN_xxxx.PDF**.

Building Safety. Building Security.



Specifications

Operating voltage	Supply through the detector line voltage
Ambient temperature	-20°C to +60°C (continuous operation) -25°C to +70°C (max. 12 hours)
Protection class	IP43 (standard) IP54 (with Protection Kit HME-ZS-IP54) IP65 (on request)
Dimensions W x H x D	126 x 126 x 35 (mm)
Colour	red, similar to RAL 3000
Weight	approx. 420g
Approvals	VdS G218045 0786-CPR-21594

Version with standardised symbol printed on it

Order number	240302
Order name	Manual Call Point/Red/Conventional HME/3000/11/H1/02

Version with door label

Lettering	house symbol + FEUER (front side) house symbol (back side)
Order number	240312
Order name	Manual Call Point/red/Conventional/FIRE HME/3000/11/52/02

Version with standardised symbol printed on it, second switch

Contact rating 2nd change-over contact	max. 2A/25VAC or 2A/30VDC
Order number	240352
Order name	Manual Call Point/red/S2/Conventional HME/3000/12/H1/02

Version with door label, second switch

Contact rating 2nd change-over contact	max. 2A/25VAC or 2A/30VDC
Lettering	house symbol + FEUER (front side) house symbol (back side)
Order number	240362
Order name	Manual Call Point/S2/Conventional/FEUER HME/3000/12/52/02

